Single Jacket Lay-flat Fire Hose - UL Listed



LISTED
EX27349

Description:

EMACO single jacket fire hose consists of plain-woven synthetic and TPU linings. The warp is made by high strength polyester staple. And the weft is high strength polyester filament with low elongation, plain or twill woven. This fire hose has very good resistance to ageing and abrasion with special adhesion between the jacket and the rubber.

Features:

- 100% Polyester Jacket, TPU rubber lined
- Maintenance free, highly flexible and light weight.
- Size Ø 1.5" & 2.5",
- Available Length: 15m (50ft) to 30m (100ft) with Aluminium BS336 Instantaneous coupling

Options

- can be provided in custom length with various coupling of Brass or Aluminium according to requirements

Application

Used at fire hydrants, standpipes, and similar places and also for wash down, maintenance, mill discharge, and construction.

Double Jacket Lay-flat Fire Hose – UL Listed



LISTED
EX27348

Description

EMACO Fire Hose is Manufactured in accordance with UL19, NFPA1961, as circularly woven jacket, with specially formulated Elastomeric red coating for protection against abrasion, mild chemicals and heat. It is soft and highly polished to reduce the flow resistance

Features:

- 100% Virgin Polyester Jacket, EPDM rubber lined
- Maintenance free, highly flexible and light weight.
- Size Ø 1.5" & 2.5",
- Available Length: 15m (50ft) to 30m (100ft) with Aluminium BS336 Instantaneous coupling

Options

- can be provided in custom length with various coupling of Brass or Aluminium according to requirements

Application

Used for Industrial and Municipal firefighting, also for Military, Commercial, Civil Engineering and Agricultural fluid transmission.

Single Jacket Lay-flat Fire Hose - Standard

Description:

EMACO single jacket fire hose consists of plain-woven synthetic and TPU linings. The warp is made by high strength polyester staple. And the weft is high strength polyester filament with low elongation, plain or twill woven. This fire hose has very good resistance to ageing and abrasion with special adhesion between the jacket and the rubber.

Features:

- 100% Polyester Jacket, TPU rubber lined
- Maintenance free, highly flexible and light weight.
- Size Ø 1.5" & 2.5",
- Available Length: 15m (50ft) to 30m (100ft) with Aluminium BS336 Instantaneous coupling

Options

- can be provided in custom length with various coupling of brass or Aluminium according to requirements



Application

Used at fire hydrants, standpipes, and similar places and also for wash down, maintenance, mill discharge, and construction.

Double Jacket Lay-flat Fire Hose – Standard

Description

EMACO Fire Hose is Manufactured in accordance with NFPA1961, as circularly woven jacket, with specially formulated Elastomeric red coating for protection against abrasion, mild chemicals and heat. It is soft and highly polished to reduce the flow resistance

Features

- 100% Virgin Polyester Jacket, EPDM rubber lined
- Maintenance free, highly flexible and light weight.
- Size Ø 1.5" & 2.5",
- Available Length: 15m (50ft) to 30m (100ft) with Aluminium BS336 Instantaneous coupling

Options

- can be provided in custom length with various coupling of brass or Aluminium according to requirements



Application

Used for Industrial and Municipal firefighting, also for Military, Commercial, Civil Engineering and Agricultural fluid transmission